









OceanLED X-Series is a superb underwater LED light range for small and medium sized fishing and cruising boats.

KEY FEATURES



Up To 1,150 Fixture Lumens



60° Top Beam



60° Side Beam



Circular Beam

COLOUR PART#



Ultra White 012301W



Midnight Blue 012302B

The OceanLED X-Series X4 combines brightness with affordability.

Whether cruising or fishing, the X4 gives stunning performance, allowing you to enjoy more time on the water with family and friends.

The X4 outputs an impressive 1,150 fixture lumens from its low profile design and utilizes focused optics to produce a 60° circular beam from each LED, providing great water penetration and illuminating a large area.

Choose Midnight Blue or Ultra White colour options.

Looking to catch more fish? Switch on the Fish-Strobe mode and the light emits a random strobe pattern that is proven to attract extra bait and help catch more fish.

- Midnight Blue and Ultra White colour options.
- Slim design makes it simple to install on small and medium sized boats.
- True 60° beam angle with no fading at the edge giving better illumination.

ABOVE WATER MOUNTING

The X Series can also be used as an exterior light for your cockpit, deck or trailer.

COMPACT AND SIMPLE DESIGN

Made from a chemically resistant optical polymer with a built in driver, there is a lot packed into this compact light.

SIMPLE TO INSTALL

Installation needs only a small, 12.5mm hole in the hull to feed the cable through and 4 screws to hold in place. No bonding required.

EASY TO CLEAN

Thanks to its Tritonium coating, a simple wipe of the lens removes any underwater growth, saving hours of scrubbing each time you use your boat.

FISH-STROBE MODE

Exceptionally bright, randomised strobing of the light is proven to attract more fish and catch more bait.

ACTIVE THERMAL CONTROL

ATC prevents overheating. In the event of overheating the ATC system will reduce the LED power level in order to protect the LEDs, or in extreme cases, turn off the fixture completely.

X4 SPECIFICATIONS

BOX CONTENTS

X-Series LED Light and Cable


In-line Fuse Kit

Mounting Screws

Material

Quick Install Guide

Quick Install Guide	
ACCESSORIES	PART
316L Stainless Steel Bezel X4	011416
4 Way V DC Power Junction Box	019901
MOUNTING RECOMMENDATIONS	
Boat size	Up to 30' (9m)
Transom / Hull spacing	2-3' (0.5-1m)
Transom quantity	2-4
Installation depth (To top of fixture)	4-8in (10-20cm)
TECHNICAL	
Lumens	1450
Fixture Lumens	1150
Typical LED life expectancy	40,000+ Hours
Minimum-Maximum operating voltage DC	9-32V DC
Current / Amp draw (DC)	12V DC 0.8A 24V DC 0.4A
Approx. light penetration (avg. water quality)	20' (6m)
Approx. Light penetration (Perfect water quality)	Up to 45' (13+m)
Driver type	Internal, Reverse Polarity Protected
PHYSICAL	
Total weight	350g (0.78lbs)
Extension cable length (standard)	9.84' (3m)
Hole cut-out for cable entry	0.5" (12.5mm)



^{*}Fixture Lumens rating is a measurement of total light output from a finished lighting fixture. This measurement can only be obtained from either a Goniophotometer or an Integrating sphere. Fixture Lumens is the most reliable, professional measurement of light output.

Chemically resistant

optical polymer