



E6 EXPLORE PRODUCT GUIDE XCHANGEABLE FLUSH MOUNT



BENEFITS OF OCEANLED REFLECTOR OPTICS

Superior Light Distribution Due To Advanced Optics

- New generation innovative, efficient reflector optics.
- Focused side beam produces a blade of light under the water that penetrates further.
- All available light is directed with minimal loss.



Explore Series Defined 90° x 20° Beam

The defined 90° beam, using advanced reflector optics, when viewed from above reduces the dark areas close to the hull.



XCHANGEABLE FLUSH MOUNT (XFM)

XFM models, or Xchangeable Flush Mount, are just that they are exchangeable without hauling should servicing ever be needed



INTERNAL DRIVER

The compact size and built in driver mean less space is required inside the boat, allowing installation in tight areas.

LOW PROFILE

The ultra low profile bezel has no effect of the flow of water against the hull.



EXPLORE E6 HALO EFFECT



OceanLED Product Guide / Explore Series / E6 / 080720 / v1.0 Specifications are subject to change without notice. Trademarks are the property of OceanLED

EXPLORE E6 CHOOSE YOUR LIGHT SETUP



EXPLORE XFM ACCESSORIES

Isolation Kit

Isolation Kit (001-500638) must be used if installing the E6 on metal, carbon fibre and wooden hulled yachts.



Extension Kit

Extension kit is required for hulls thicker than 55mm.



CONTROL OPTIONS SCHEMATIC



Built In Fault Finding

The Explore E6 lights have a built-in rear indicator LED. The LED confirms the light is working within designed parameters, and in the case of a fault, will indicate information as to the root cause.

OCEANLED CUSTOM PROJECT SUPPORT

OceanLED has an in house dedicated customer service, sales and engineering team on hand to support our Superyacht clients in various stages of the build. With 2D and parametric 3D CAD facilities, OceanLED will follow projects from inception through to launch to ensure the best possible solution.

Ocean LED Marine LTD / Tel +44 (0) 1455 637505 / sales@oceanled.com

#012926 Control Link Cable (10m)

> uired (N.B. 1 cable than No. of lights)

#012928 Control Link Cable (20m)

> d (N.B. 1 cable an No. of lights

#012927 Control Link Cable (15m)

> (N.B. 1 cable No of lights